

## PS4

### Access Doors

#### SPECIFICATION

- > 24" x 60" Door size (20" x 56" clear opening)
- > 12" x 12" double pane Plexiglas window
- > Quantity of 2 Ventlok 310 handles and 2 plated butt hinges
- > Neoprene bulb gasket door seal
- > 16 ga solid galvanized outside sheet; 22 ga solid galvanized steel inside sheet; 12 ga galvanized steel frame

#### ADVANTAGES

- > Doors are pre-hung in frame with attached closure hardware
- > Easily installed in minimum of time
- > Quality seals – resists moisture, air and noise leakage
- > Excellent installed appearance
- > Superior strength

#### APPLICATIONS

- > Access for rooms and booths
- > Access for Air handling units and plenums

#### CONSTRUCTION

- > Minimum 12 ga galvanized steel formed frame
- > Maximum 10 ga galvanized or stainless steel face sheet
- > Maximum 10 ga galvanized or stainless steel solid inside sheet
- > Thermal/Acoustical material sandwiched between skins
- > Internal stiffening of door
- > Plated 4" x 4.5" in ball bearing butt hinges
- > Two Ventlok 310 handles
- > Floating hinge mounts, for field adjustment
- > Bulb gasket for perimeter seal
- > Inside pull

#### OPTIONS

- > Door sizes and thicknesses to suit requirements
- > Double door arrangements
- > Alternate materials
- > Doubled paned windows
- > Windows with wired or tempered glass, Lexan or acrylic panes
- > Thermal breaks on through metal
- > Piano hinges – plated or stainless steel
- > Automotive style hinges and latches
- > Heavy duty / industrial latches
- > Neoprene or FDA white perimeter seal gasket

