


RFMB-HV-F1

Rectangular Film MoldBlock
High velocity silencer
(<2000 fpm)

How to Specify Example:

32 X 21 RFMB-HV-F1 X 60
 ↑ Duct Width ↑ Duct Height ↑ Silencer Model ↑ Silencer Length



Insertion Loss (IL)

+ : "forward flow" where noise & airflow move in same direction (e.g. supply side)

- : "reverse flow" where noise & airflow move in opposite directions (e.g. return side)

See [Silencer Selection Instructions](#). DIL above 50dB may be limited due to noise flanking around the silencer or along the duct walls. If more than 50dB DIL is required, contact your local Vibro-Acoustics Representative or call **1-800-565-8401**.

Length (in.)	Face Velocity (ft. per min)	Octave Band - Hz/Dynamic Insertion Loss (dB)							
		63	125	250	500	1000	2000	4000	8000
36	- 2000	2	5	10	12	12	13	13	8
	+ 2000	2	3	8	11	11	11	11	6
60	- 2000	5	7	11	14	18	19	13	8
	+ 2000	4	5	10	13	17	17	13	7
84	- 2000	8	9	13	16	24	24	14	8
	+ 2000	7	6	11	14	24	23	15	8
108	- 2000	10	11	16	20	29	28	16	8
	+ 2000	8	8	14	18	29	27	17	9

Pressure Drop (PD)

Pressure drops are reported in accordance with ASTM E477 methods and are based upon **ideal** flow conditions (5 diameters of straight duct on silencer inlet and 10 on outlet). Less than ideal conditions will result in an increase in pressure drop due to System Effects. See [Silencer System Effects Data](#).

Length (in.)	Face Velocity (ft. per min) / Pressure Drop (in.w.g.)						
	500	1000	1500	1750	2000	2250	2500
36	0.01	0.04	0.09	0.12	0.16	0.20	0.25
60	0.01	0.05	0.12	0.17	0.22	0.28	0.34
84	0.02	0.07	0.16	0.21	0.28	0.35	0.44
108	0.02	0.09	0.19	0.26	0.34	0.43	0.53

Acceptable (0 - 0.35") Caution (>0.35") Pressure Drop may be too high for certain applications

Generated Noise (GN)

@ 5 sq.ft. face area

Length (in.)	Face Velocity (ft. per min)	Octave Band - Hz/Generated Noise (dB re 10 ⁻¹² watts)							
		63	125	250	500	1K	2K	4K	8K
All	- 2000	58	54	54	53	54	55	47	38
	- 1250	54	49	47	47	47	44	33	26
	+ 1250	58	47	42	43	42	39	28	25
	+ 2000	60	56	52	52	51	53	46	36

GN correction chart at right must be used to correct GN to other face areas. →

Face Area (sq.ft.)	2.5	5	10	20	40	80
dB	-3	0	+3	+6	+9	+12

Cross Section Sizes*

"A" dimension (in.)

14.5–15.5
29–31
58–62
87–93
116–124
145–155
174–186
203–217
232–248

"B" dimension ANY SIZE


See [Rectangular Silencer Cross-Section Dimensions](#) to ensure selection matches ductwork dimensions.

RFMB-HV-F2

Rectangular Film MoldBlock
High velocity silencer
(<2000 fpm)

How to Specify Example:

27 X 22 RFMB-HV-F2 X 60
 ↑ Duct Width ↑ Duct Height ↑ Silencer Model ↑ Silencer Length



Insertion Loss (IL)

+ : "forward flow" where noise & airflow move in same direction (e.g. supply side)

- : "reverse flow" where noise & airflow move in opposite directions (e.g. return side)

See [Silencer Selection Instructions](#). DIL above 50dB may be limited due to noise flanking around the silencer or along the duct walls. If more than 50dB DIL is required, contact your local Vibro-Acoustics Representative or call **1-800-565-8401**.

Length (in.)	Face Velocity (ft. per min)	Octave Band - Hz/Dynamic Insertion Loss (dB)							
		63	125	250	500	1000	2000	4000	8000
36	- 2000	3	5	9	13	13	12	11	7
	+ 2000	1	3	8	11	12	11	10	6
60	- 2000	6	6	10	15	19	19	13	7
	+ 2000	4	4	9	13	18	18	12	6
84	- 2000	9	8	12	17	26	25	14	7
	+ 2000	7	6	10	15	25	25	14	7
108	- 2000	10	10	15	22	32	29	15	8
	+ 2000	7	8	14	20	32	29	16	8

Pressure Drop (PD)

Pressure drops are reported in accordance with ASTM E477 methods and are based upon **ideal** flow conditions (5 diameters of straight duct on silencer inlet and 10 on outlet). Less than ideal conditions will result in an increase in pressure drop due to System Effects. See [Silencer System Effects Data](#).

Length (in.)	Face Velocity (ft. per min) / Pressure Drop (in.w.g.)						
	500	1000	1500	1750	2000	2250	2500
36	0.01	0.04	0.09	0.12	0.16	0.20	0.25
60	0.01	0.05	0.12	0.16	0.21	0.27	0.33
84	0.02	0.07	0.16	0.21	0.28	0.35	0.44
108	0.02	0.08	0.18	0.24	0.32	0.40	0.50

Acceptable (0 - 0.35") Caution (>0.35") Pressure Drop may be too high for certain applications

Generated Noise (GN)

@ 5 sq.ft. face area

Length (in.)	Face Velocity (ft. per min)	Octave Band - Hz/Generated Noise (dB re 10 ⁻¹² watts)							
		63	125	250	500	1K	2K	4K	8K
All	- 2000	58	55	54	54	55	56	47	38
	- 1250	53	50	47	48	47	44	33	26
	+ 1250	57	48	42	43	42	39	28	25
	+ 2000	60	57	53	52	51	53	47	37

GN correction chart at right must be used to correct GN to other face areas. →

Face Area (sq.ft.)	2.5	5	10	20	40	80
dB	-3	0	+3	+6	+9	+12

Cross Section Sizes*

"A" dimension (in.)

13.5-14.5
27-29
54-58
81-87
108-116
135-145
162-174
189-203
216-232

"B" dimension ANY SIZE


See [Rectangular Silencer Cross-Section Dimensions](#) to ensure selection matches ductwork dimensions.

RFMB-HV-F3

Rectangular Film MoldBlock
High velocity silencer
(<2000 fpm)

How to Specify Example:

25 X 21 RFMB-HV-F3 X 60
 ↑ Duct Width ↑ Duct Height ↑ Silencer Model ↑ Silencer Length



Insertion Loss (IL)

+ : "forward flow" where noise & airflow move in same direction (e.g. supply side)

- : "reverse flow" where noise & airflow move in opposite directions (e.g. return side)

See [Silencer Selection Instructions](#). DIL above 50dB may be limited due to noise flanking around the silencer or along the duct walls. If more than 50dB DIL is required, contact your local Vibro-Acoustics Representative or call **1-800-565-8401**.

Length (in.)	Face Velocity (ft. per min)	Octave Band - Hz/Dynamic Insertion Loss (dB)							
		63	125	250	500	1000	2000	4000	8000
36	- 2000	3	4	9	13	13	12	10	6
	+ 2000	1	3	7	12	13	11	9	5
60	- 2000	7	6	10	15	21	19	12	6
	+ 2000	4	4	8	14	19	19	12	6
84	- 2000	10	8	11	17	28	26	14	7
	+ 2000	7	6	9	15	26	28	14	6
108	- 2000	9	10	15	24	35	31	15	7
	+ 2000	6	8	13	22	35	32	15	8

Pressure Drop (PD)

Pressure drops are reported in accordance with ASTM E477 methods and are based upon **ideal** flow conditions (5 diameters of straight duct on silencer inlet and 10 on outlet). Less than ideal conditions will result in an increase in pressure drop due to System Effects. See [Silencer System Effects Data](#).

Length (in.)	Face Velocity (ft. per min) / Pressure Drop (in.w.g.)						
	500	1000	1500	1750	2000	2250	2500
36	0.01	0.04	0.09	0.12	0.16	0.20	0.25
60	0.01	0.05	0.12	0.16	0.21	0.26	0.32
84	0.02	0.07	0.16	0.21	0.28	0.35	0.44
108	0.02	0.08	0.17	0.23	0.30	0.38	0.47

Acceptable (0 - 0.35") Caution (>0.35") Pressure Drop may be too high for certain applications

Generated Noise (GN)

@ 5 sq.ft. face area

Length (in.)	Face Velocity (ft. per min)	Octave Band - Hz/Generated Noise (dB re 10 ⁻¹² watts)							
		63	125	250	500	1K	2K	4K	8K
All	- 2000	57	55	55	54	55	56	48	38
	- 1250	53	50	47	48	48	44	33	25
	+ 1250	57	49	43	43	42	40	29	25
	+ 2000	59	58	54	52	51	53	47	38

GN correction chart at right must be used to correct GN to other face areas. →

Face Area (sq.ft.)	2.5	5	10	20	40	80
dB	-3	0	+3	+6	+9	+12

Cross Section Sizes*

"A" dimension (in.)
 12.5-13.5
 25-27
 50-54
 75-81
 100-108
 125-135
 150-162
 175-189
 200-216
 225-243

"B" dimension
 ANY SIZE

See [Rectangular Silencer Cross-Section Dimensions](#) to ensure selection matches ductwork dimensions.


RFMB-HV-F4

Rectangular Film MoldBlock
High velocity silencer
(<2000 fpm)

How to Specify Example:

47 × **22** **RFMB-HV-F4** × **60**

↑ Duct Width ↑ Duct Height ↑ Silencer Model ↑ Silencer Length



Insertion Loss (IL)

+ : "forward flow" where noise & airflow move in same direction (e.g. supply side)

- : "reverse flow" where noise & airflow move in opposite directions (e.g. return side)

See [Silencer Selection Instructions](#). DIL above 50dB may be limited due to noise flanking around the silencer or along the duct walls. If more than 50dB DIL is required, contact your local Vibro-Acoustics Representative or call **1-800-565-8401**.

Length (in.)	Face Velocity (ft. per min)	Octave Band - Hz/Dynamic Insertion Loss (dB)							
		63	125	250	500	1000	2000	4000	8000
36	- 2000	3	4	8	13	14	11	9	5
	+ 2000	1	3	7	12	13	11	8	4
60	- 2000	7	6	9	16	22	19	11	6
	+ 2000	4	4	7	14	20	21	11	5
84	- 2000	11	7	10	18	31	27	14	7
	+ 2000	8	5	8	16	27	30	13	6
108	- 2000	8	10	15	26	37	32	14	6
	+ 2000	5	8	13	24	38	34	14	7

Pressure Drop (PD)

Pressure drops are reported in accordance with ASTM E477 methods and are based upon **ideal** flow conditions (5 diameters of straight duct on silencer inlet and 10 on outlet). Less than ideal conditions will result in an increase in pressure drop due to System Effects. See [Silencer System Effects Data](#).

Length (in.)	Face Velocity (ft. per min) / Pressure Drop (in.w.g.)						
	500	1000	1500	1750	2000	2250	2500
36	0.01	0.04	0.09	0.12	0.16	0.20	0.25
60	0.01	0.05	0.11	0.15	0.20	0.25	0.31
84	0.02	0.07	0.16	0.21	0.28	0.35	0.44
108	0.02	0.07	0.16	0.21	0.28	0.34	0.44

Acceptable (0 - 0.35")

Caution (>0.35") Pressure Drop may be too high for certain applications

Generated Noise (GN)

@ 5 sq.ft. face area

Length (in.)	Face Velocity (ft. per min)	Octave Band - Hz/Generated Noise (dB re 10 ⁻¹² watts)							
		63	125	250	500	1K	2K	4K	8K
All	- 2000	56	56	55	54	55	56	48	37
	- 1250	53	50	47	48	48	44	32	25
	+ 1250	56	49	44	43	42	40	29	25
	+ 2000	59	59	54	52	51	54	48	39

GN correction chart at right must be used to correct GN to other face areas. →

Face Area (sq.ft.)	2.5	5	10	20	40	80
dB	-3	0	+3	+6	+9	+12

Cross Section Sizes*

"A" dimension (in.)

11.5–12.5
23–25
46–50
69–75
92–100
115–125
138–150
161–175
207–225

"B" dimension ANY SIZE

See [Rectangular Silencer Cross-Section Dimensions](#) to ensure selection matches ductwork dimensions.


RFMB-HV-F5

Rectangular Film MoldBlock
High velocity silencer
(<2000 fpm)

How to Specify Example:

44 X **22** **RFMB-HV-F5** X **60**

↑ Duct Width ↑ Duct Height ↑ Silencer Model ↑ Silencer Length



Insertion Loss (IL)

+ : "forward flow" where noise & airflow move in same direction (e.g. supply side)

- : "reverse flow" where noise & airflow move in opposite directions (e.g. return side)

See [Silencer Selection Instructions](#). DIL above 50dB may be limited due to noise flanking around the silencer or along the duct walls. If more than 50dB DIL is required, contact your local Vibro-Acoustics Representative or call **1-800-565-8401**.

Length (in.)	Face Velocity (ft. per min)	Octave Band - Hz/Dynamic Insertion Loss (dB)							
		63	125	250	500	1000	2000	4000	8000
36	- 2000	3	4	8	13	15	14	10	5
	+ 2000	1	3	7	11	14	14	10	4
60	- 2000	7	6	9	16	24	22	13	6
	+ 2000	4	4	7	14	21	23	13	5
84	- 2000	11	7	10	20	32	30	16	7
	+ 2000	7	5	8	17	28	32	16	6
108	- 2000	8	10	15	27	38	34	16	6
	+ 2000	4	7	13	24	39	37	17	6

Pressure Drop (PD)

Pressure drops are reported in accordance with ASTM E477 methods and are based upon **ideal** flow conditions (5 diameters of straight duct on silencer inlet and 10 on outlet). Less than ideal conditions will result in an increase in pressure drop due to System Effects. See [Silencer System Effects Data](#).

Length (in.)	Face Velocity (ft. per min) / Pressure Drop (in.w.g.)						
	500	1000	1500	1750	2000	2250	2500
36	0.01	0.04	0.09	0.12	0.16	0.20	0.25
60	0.01	0.05	0.12	0.16	0.21	0.26	0.32
84	0.02	0.08	0.17	0.23	0.31	0.39	0.48
108	0.02	0.07	0.16	0.22	0.29	0.37	0.46

Acceptable (0 - 0.35") Caution (>0.35") Pressure Drop may be too high for certain applications

Generated Noise (GN)

@ 5 sq.ft. face area

Length (in.)	Face Velocity (ft. per min)	Octave Band - Hz/Generated Noise (dB re 10 ⁻¹² watts)							
		63	125	250	500	1K	2K	4K	8K
All	- 2000	56	56	55	55	55	57	49	39
	- 1250	53	50	47	48	48	45	33	25
	+ 1250	56	49	44	44	43	40	29	25
	+ 2000	59	59	54	53	52	53	48	40

GN correction chart at right must be used to correct GN to other face areas. →

Face Area (sq.ft.)	2.5	5	10	20	40	80
dB	-3	0	+3	+6	+9	+12

Cross Section Sizes*

"A" dimension (in.)
10.5–11.5
21–23
42–46
63–69
84–92
105–115
126–138
147–161
168–184
189–207

"B" dimension
ANY SIZE

See [Rectangular Silencer Cross-Section Dimensions](#) to ensure selection matches ductwork dimensions.


RFMB-HV-F6

Rectangular Film MoldBlock
High velocity silencer
(<2000 fpm)

How to Specify Example:

40 X **21** **RFMB-HV-F6** X **60**

↑ Duct Width ↑ Duct Height ↑ Silencer Model ↑ Silencer Length



Insertion Loss (IL)

+ : "forward flow" where noise & airflow move in same direction (e.g. supply side)

- : "reverse flow" where noise & airflow move in opposite directions (e.g. return side)

See [Silencer Selection Instructions](#). DIL above 50dB may be limited due to noise flanking around the silencer or along the duct walls. If more than 50dB DIL is required, contact your local Vibro-Acoustics Representative or call **1-800-565-8401**.

Length (in.)	Face Velocity (ft. per min)	Octave Band - Hz/Dynamic Insertion Loss (dB)							
		63	125	250	500	1000	2000	4000	8000
36	- 2000	3	4	7	12	15	16	11	5
	+ 2000	1	3	6	11	14	16	11	4
60	- 2000	7	6	9	16	25	24	15	6
	+ 2000	4	4	7	15	22	26	14	6
84	- 2000	10	7	11	21	34	32	18	8
	+ 2000	7	6	9	18	30	35	18	7
108	- 2000	7	10	15	27	39	36	18	7
	+ 2000	4	7	12	24	29	39	20	8

Pressure Drop (PD)

Pressure drops are reported in accordance with ASTM E477 methods and are based upon **ideal** flow conditions (5 diameters of straight duct on silencer inlet and 10 on outlet). Less than ideal conditions will result in an increase in pressure drop due to System Effects. See [Silencer System Effects Data](#).

Length (in.)	Face Velocity (ft. per min) / Pressure Drop (in.w.g.)						
	500	1000	1500	1750	2000	2250	2500
36	0.01	0.04	0.09	0.12	0.16	0.20	0.25
60	0.01	0.05	0.12	0.16	0.21	0.27	0.33
84	0.02	0.08	0.19	0.26	0.33	0.42	0.52
108	0.02	0.08	0.17	0.23	0.31	0.39	0.48

Acceptable (0 - 0.35") Caution (>0.35") Pressure Drop may be too high for certain applications

Cross Section Sizes*
"A" dimension (in.)
9.5–10.5
19–21
38–42
57–63
76–84
95–105
114–126
133–147
152–168
171–189

Generated Noise (GN)

@ 5 sq.ft. face area

Length (in.)	Face Velocity (ft. per min)	Octave Band - Hz/Generated Noise (dB re 10 ⁻¹² watts)							
		63	125	250	500	1K	2K	4K	8K
All	- 2000	56	55	56	55	55	58	50	40
	- 1250	52	50	47	48	49	46	34	26
	+ 1250	56	49	44	44	43	39	29	25
	+ 2000	59	58	55	53	52	53	48	41

GN correction chart at right must be used to correct GN to other face areas. →

Face Area (sq.ft.)	2.5	5	10	20	40	80
dB	-3	0	+3	+6	+9	+12

"B" dimension ANY SIZE


See [Rectangular Silencer Cross-Section Dimensions](#) to ensure selection matches ductwork dimensions.

RFMB-HV-F7

Rectangular Film MoldBlock
High velocity silencer
(<2000 fpm)

How to Specify Example:

37 X 21 RFMB-HV-F7 X 60
 ↑ Duct Width ↑ Duct Height ↑ Silencer Model ↑ Silencer Length



Insertion Loss (IL)

+ : "forward flow" where noise & airflow move in same direction (e.g. supply side)

- : "reverse flow" where noise & airflow move in opposite directions (e.g. return side)

See [Silencer Selection Instructions](#). DIL above 50dB may be limited due to noise flanking around the silencer or along the duct walls. If more than 50dB DIL is required, contact your local Vibro-Acoustics Representative or call **1-800-565-8401**.

Length (in.)	Face Velocity (ft. per min)	Octave Band - Hz/Dynamic Insertion Loss (dB)							
		63	125	250	500	1000	2000	4000	8000
36	- 2000	3	4	7	12	16	19	12	5
	+ 2000	1	3	6	10	15	18	12	4
60	- 2000	6	6	9	17	26	27	16	7
	+ 2000	4	4	7	15	23	28	16	6
84	- 2000	10	8	12	22	36	35	20	8
	+ 2000	6	6	9	19	32	38	21	7
108	- 2000	7	9	15	27	39	38	19	7
	+ 2000	4	7	12	25	40	41	22	9

Pressure Drop (PD)

Pressure drops are reported in accordance with ASTM E477 methods and are based upon **ideal** flow conditions (5 diameters of straight duct on silencer inlet and 10 on outlet). Less than ideal conditions will result in an increase in pressure drop due to System Effects. See [Silencer System Effects Data](#).

Length (in.)	Face Velocity (ft. per min) / Pressure Drop (in.w.g.)						
	500	1000	1500	1750	2000	2250	2500
36	0.01	0.04	0.09	0.12	0.16	0.20	0.25
60	0.01	0.06	0.12	0.17	0.22	0.28	0.34
84	0.02	0.09	0.20	0.28	0.36	0.46	0.56
108	0.02	0.08	0.18	0.24	0.32	0.40	0.50

Acceptable (0 - 0.35") Caution (>0.35") Pressure Drop may be too high for certain applications

Generated Noise (GN)

@ 5 sq.ft. face area

Length (in.)	Face Velocity (ft. per min)	Octave Band - Hz/Generated Noise (dB re 10 ⁻¹² watts)							
		63	125	250	500	1K	2K	4K	8K
All	- 2000	56	55	56	55	56	58	52	41
	- 1250	52	50	46	48	49	47	35	26
	+ 1250	56	49	44	45	44	39	29	25
	+ 2000	59	58	55	54	53	53	48	42

GN correction chart at right must be used to correct GN to other face areas. →

Face Area (sq.ft.)	2.5	5	10	20	40	80
dB	-3	0	+3	+6	+9	+12

Cross Section Sizes*

"A" dimension (in.)
 8.25-9.5
 16.5-19
 33-38
 49.5-57
 66-76
 82.5-95
 99-114
 115.5-133
 132-152
 148.5-171

"B" dimension ANY SIZE


See [Rectangular Silencer Cross-Section Dimensions](#) to ensure selection matches ductwork dimensions.

RFMB-HV-F8

Rectangular Film MoldBlock
High velocity silencer
(<2000 fpm)

How to Specify Example:

14 X 22 RFMB-HV-F8 X 60
 ↑ Duct Width ↑ Duct Height ↑ Silencer Model ↑ Silencer Length



Insertion Loss (IL)

+ : "forward flow" where noise & airflow move in same direction (e.g. supply side)

- : "reverse flow" where noise & airflow move in opposite directions (e.g. return side)

See [Silencer Selection Instructions](#). DIL above 50dB may be limited due to noise flanking around the silencer or along the duct walls. If more than 50dB DIL is required, contact your local Vibro-Acoustics Representative or call **1-800-565-8401**.

Length (in.)	Face Velocity (ft. per min)	Octave Band - Hz/Dynamic Insertion Loss (dB)							
		63	125	250	500	1000	2000	4000	8000
36	- 2000	2	4	7	11	14	21	17	8
	+ 2000	1	3	5	9	14	20	17	8
60	- 2000	5	5	10	17	25	24	18	8
	+ 2000	3	4	8	15	24	26	19	8
84	- 2000	7	6	13	24	35	28	18	8
	+ 2000	5	5	11	22	34	31	21	9
108	- 2000	9	8	17	31	42	35	21	9
	+ 2000	7	6	14	28	42	39	25	10

Pressure Drop (PD)

Pressure drops are reported in accordance with ASTM E477 methods and are based upon **ideal** flow conditions (5 diameters of straight duct on silencer inlet and 10 on outlet). Less than ideal conditions will result in an increase in pressure drop due to System Effects. See [Silencer System Effects Data](#).

Length (in.)	Face Velocity (ft. per min) / Pressure Drop (in.w.g.)						
	500	1000	1500	1750	2000	2250	2500
36	0.01	0.05	0.10	0.14	0.18	0.23	0.28
60	0.02	0.07	0.15	0.21	0.27	0.34	0.42
84	0.02	0.09	0.20	0.28	0.36	0.46	0.56
108	0.03	0.11	0.25	0.34	0.45	0.57	0.70

Acceptable (0 - 0.35") Caution (>0.35") Pressure Drop may be too high for certain applications

Generated Noise (GN)

@ 5 sq.ft. face area

Length (in.)	Face Velocity (ft. per min)	Octave Band - Hz/Generated Noise (dB re 10 ⁻¹² watts)							
		63	125	250	500	1K	2K	4K	8K
All	- 2000	58	55	56	56	57	58	53	45
	- 1250	53	47	47	49	48	46	35	28
	+ 1250	57	4	43	46	45	36	27	26
	+ 2000	60	57	54	55	55	51	46	40

GN correction chart at right must be used to correct GN to other face areas. →

Face Area (sq.ft.)	2.5	5	10	20	40	80
dB	-3	0	+3	+6	+9	+12

Cross Section Sizes*

"A" dimension (in.)
6.75–8.25
13.5–16.5
27–33
40.5–49.5
54–66
67.5–82.5
81–99
94.5–115.5
108–132
121.5–148.5

"B" dimension
ANY SIZE

See [Rectangular Silencer Cross-Section Dimensions](#) to ensure selection matches ductwork dimensions.


RFMB-HV-F9

Rectangular Film MoldBlock
High velocity silencer
(<2000 fpm)

How to Specify Example:

21 X 21 RFMB-HV-F9 X 60

↑ Duct Width ↑ Duct Height ↑ Silencer Model ↑ Silencer Length



Insertion Loss (IL)

+ : "forward flow" where noise & airflow move in same direction (e.g. supply side)

- : "reverse flow" where noise & airflow move in opposite directions (e.g. return side)

See [Silencer Selection Instructions](#). DIL above 50dB may be limited due to noise flanking around the silencer or along the duct walls. If more than 50dB DIL is required, contact your local Vibro-Acoustics Representative or call **1-800-565-8401**.

Length (in.)	Face Velocity (ft. per min)	Octave Band - Hz/Dynamic Insertion Loss (dB)							
		63	125	250	500	1000	2000	4000	8000
36	- 2000	2	4	6	10	18	26	15	6
	+ 2000	1	3	4	8	16	25	15	5
60	- 2000	5	6	10	18	29	35	21	8
	+ 2000	3	4	7	15	26	35	21	7
84	- 2000	8	8	14	26	41	44	27	10
	+ 2000	5	6	10	22	36	45	28	9
108	- 2000	6	8	15	29	41	44	25	8
	+ 2000	4	6	11	25	42	48	30	10

Pressure Drop (PD)

Pressure drops are reported in accordance with ASTM E477 methods and are based upon **ideal** flow conditions (5 diameters of straight duct on silencer inlet and 10 on outlet). Less than ideal conditions will result in an increase in pressure drop due to System Effects. See [Silencer System Effects Data](#).

Length (in.)	Face Velocity (ft. per min) / Pressure Drop (in.w.g.)						
	500	1000	1500	1750	2000	2250	2500
36	0.01	0.04	0.09	0.12	0.16	0.20	0.25
60	0.02	0.06	0.13	0.18	0.24	0.30	0.37
84	0.03	0.11	0.25	0.34	0.44	0.56	0.69
108	0.02	0.09	0.20	0.28	0.36	0.46	0.56

Acceptable (0 - 0.35") Caution (>0.35") Pressure Drop may be too high for certain applications

Generated Noise (GN)

@ 5 sq.ft. face area

Length (in.)	Face Velocity (ft. per min)	Octave Band - Hz/Generated Noise (dB re 10 ⁻¹² watts)							
		63	125	250	500	1K	2K	4K	8K
All	- 2000	56	55	57	55	56	60	55	45
	- 1250	52	49	45	48	50	49	38	27
	+ 1250	56	48	43	46	45	38	29	26
	+ 2000	59	58	55	55	54	52	48	44

GN correction chart at right must be used to correct GN to other face areas. →

Face Area (sq.ft.)	2.5	5	10	20	40	80
dB	-3	0	+3	+6	+9	+12

Cross Section Sizes*

"A" dimension (in.)
5-6.75
10-13.5
20-27
30-40.5
40-54
50-67.5
60-81
70-94.5
80-108
90-121.5

"B" dimension
ANY SIZE

See [Rectangular Silencer Cross-Section Dimensions](#) to ensure selection matches ductwork dimensions.